

DECLARATION OF PERFORMANCE

DOP 70-05.01.01.20

1.	Unique identification code of the product-type:		
	Solcora® 70-05		
2.	Type, batch or serial number or any other element allowing iden	tification of the construction product as required	d pursuant to Article 11(4):
	Batch number shown on packaging		
3.	Intended use or uses of the construction product, in accordance	with the applicable harmonised technical spec	ifi- cation, as foreseen by the manufacturer:
	For use as floor covering in buildings (see EN 1	4041) according to the manufactur	er's specifications.
4.	Name, registered trade name or registered trade mark and conta	act address of the manufacturer as required pu	rsuant to Article 11(5):
	Solcora, Endesign Limited, Koppelstraat 23, 73	91 AK, Twello, The Netherlands	
5.	Where applicable, name and contact address of the authorised	representative whose mandate covers the task	s specified in Article 12(2):
	Nick Atkins, Endesign Limited, Hilltop, Barton R	oad, Pulloxhill, Bedfordshire MK45	5HP, England
6.	System or systems of assessment and verification of constancy	of performance of the construction product as	set out in Annex V:
	System 3		
7.	In case of the declaration of performance concerning a construction product covered by a harmonised standard: Name of the notified test laboratory, that has issued the certificate of conformity of the factory production control, inspection reports and calculation reports (if relevant).		
	TÜV Rheinland Nederland B.V. notify body number 0336, fire report number T11 3239703		not applicable
	Notified Body		certificate of constancy of performance
8.	In case of the declaration of performance concerning a construction	tion product for which a European Technical As	ssessment has been issued:
	not applicable		
9.	Declared performance		
	Essential characteristics		_
	Essential characteristics	Performance	Harmonised technical specification
	Reaction to fire	Performance BfI-s1	Harmonised technical specification EN 13501-1:2007
	Reaction to fire	Bfl-s1	EN 13501-1:2007
	Reaction to fire Slip resistance	Bfl-s1 DS	EN 13501-1:2007 EN 13893:2002
	Reaction to fire Slip resistance Electrical behavior (antistatic)	Bfl-s1 DS Antistatic	EN 13501-1:2007 EN 13893:2002 EN 1815:1997
10.	Reaction to fire Slip resistance Electrical behavior (antistatic) Thermal conductivity [W/mK]	BfI-s1 DS Antistatic 0,054 NPD conformity with the declared performance in po	EN 13501-1:2007 EN 13893:2002 EN 1815:1997 ISO 8302:1991 EN 13553
10.	Reaction to fire Slip resistance Electrical behavior (antistatic) Thermal conductivity [W/mK] Water-tightness The performance of the product identified in points 1 and 2 is in This declaration of performance is issued under the sole responsigned for and on behalf of the manufacturer by: Nick Atkins - Compliance Manager	BfI-s1 DS Antistatic 0,054 NPD conformity with the declared performance in po	EN 13501-1:2007 EN 13893:2002 EN 1815:1997 ISO 8302:1991 EN 13553
10.	Reaction to fire Slip resistance Electrical behavior (antistatic) Thermal conductivity [W/mK] Water-tightness The performance of the product identified in points 1 and 2 is in This declaration of performance is issued under the sole responsigned for and on behalf of the manufacturer by: Nick Atkins - Compliance Manager (name and function)	BfI-s1 DS Antistatic 0,054 NPD conformity with the declared performance in po	EN 13501-1:2007 EN 13893:2002 EN 1815:1997 ISO 8302:1991 EN 13553
10.	Reaction to fire Slip resistance Electrical behavior (antistatic) Thermal conductivity [W/mK] Water-tightness The performance of the product identified in points 1 and 2 is in This declaration of performance is issued under the sole responsigned for and on behalf of the manufacturer by: Nick Atkins - Compliance Manager	BfI-s1 DS Antistatic 0,054 NPD conformity with the declared performance in po	EN 13501-1:2007 EN 13893:2002 EN 1815:1997 ISO 8302:1991 EN 13553